

# **A Golf Club Head with Adjustable Tilt Mechanism**

## **Field of the Invention**

This invention concerns the adjustable tilt mechanism for the golf club in which the adjustable tilt mechanism is designed to mount between a shaft and a  
5 head, capable of changing the tilt angle of the face, easy for the golf player to strike the club and render the ball a flight a low or a high parabola to shun away the obstacle.

## **Background of the Invention**

10 Figs. 1 and 2 show the schematic diagrams of the prior art of a golf club that is very popular in use containing a head 10 and a vertically formed neck 11. The head has a variety of sizes and the face 12 and the neck 11 are linked in different angle. The neck 11 has a cavity 13 to receive a hosel 15 and a shaft 14 which is glued fast in the cavity 13. Besides the difference in sizes, the shaft  
15 length and gravity, the angle formed between the face 12, and the shaft 14 varies greatly too. Simply speaking, when the angle formed between the face 12 and the shaft 14 is wide obtuse, the ball will fly low parabola course. Each golf bag will at least contains the iron clubs No.1, 2, 3, 4, 5, 6, 7, 8, 9, P and 9, total nine clubs and the wood clubs No. 1, 3 and 5, three wood clubs in order to  
20 strike the ball to the green with least number of strokes. In reality, in most case in 18 holes play, because of poor control over the ball flight, the ball occasionally falls behind the obstacle (big tree) which stands between the ball and the green. Under this circumstance, the seasoned player would change his

stance and the iron club with a acute angle face, so the ball being struck would fly a high parabola flight over the obstacle, or he would change his stance and uses the large-number iron club with small angle to strike the ball flying a low parabola to penetrate through the obstacle. From the above statement, it is learned that the angle form between the face 12 of the head 10 and the shaft 14 is a critical factor to make a ball a low parabola or high parabola flight. The adjustable tilt mechanism is provided between the head and the shaft, for the unskillful player, it is easy way to promote his golf playing interest. This serves the purpose the inventor wants to design this adjustable tilt mechanism.

10

### **Summary of the Invention**

Because all golf clubs are formed at a fixed angle between the head and the shaft, it is extremely hard for the unskillful golf player to pick the right club to hit the right parabola for the ball. For this reason, the inventor, for long experience in manufacturing golf club and wide observation, has begun to come up this invention with many trials and errors. This invention designs an inverted conical long hole in the neck; the lower end of the shaft passes the retaining ring and the hosel and enters into the long adjustable hole in the neck to be locked by the lock pin with the neck. However the shaft is so permitted to swing to left or to right as to change the angle (elevation angle) between the face and the shaft but still held firmly by the retaining ring and adjustable hole in the neck.

20

### **Brief Description of the Drawings**

Fig. 1 shows an appearance of the prior art of the golf club.

Fig. 2 shows an assembly view of the prior art of the golf club.

5 Fig. 3 shows a disassembly view of an adjustable tilt mechanism of a club shaft of this invention.

Fig. 3-1 shows the side view of an adjustable tilt mechanism of a club shaft of this invention.

10

Fig. 3-2 shows the bottom view of an adjustable tilt mechanism of a club shaft of this invention.

Fig. 4 shows a schematic diagram of the adjustment of a small elevation angle  
15 in the adjustable tilt mechanism of the club shaft of this invention.

Fig. 5 is a cross section view taken along lines 5-5 of Fig. 4.

Fig. 6 shows a schematic diagram of the adjustment of a large elevation angle  
20 in the adjustable tilt mechanism of the club shaft of this invention.

Fig. 7 is a cross section view taken along lines 7-7 of Fig. 6.

### **Detailed Description of the Invention**

25 This invention will be explained in great detail with the aid of a plurality of

embodiments as illustrated in the drawings attached.

Fig. 3 shows a disassembly view of an adjustable tilt mechanism of this invention wherein the adjustable tilt mechanism comprises a head 20, a hosel  
5 30, a retaining ring 40, and a shaft 50.

As shown in the prior art of golf club, the head 20 is vertically formed with the neck 21. The head 20 is numbered in size and each size has a specified tilt formed between the face 22 and the neck 21. But in this invention, the neck 21  
10 of the head 20 provides a long adjustable hole 23 which has a wide opening and narrow bottom. The opening rim has a plurality of tie slots 24 distributed at a specific angle. A through lock hole 35 is drilled at the lower part of the neck 21 to receive the lock pin 26 so as to lock the shaft 50 in the long adjustable hole  
23.

15 The hosel 30 has a longitudinal hollow 31 in which inner diameter equals to the outer diameter of the shaft 50. The bottom face of the hosel 30 is in the similar shape of the neck top 21 of the head 20. Along the inner rim of the hosel 30, there are three tie lands 32.

20 The retaining ring 40 has an inner thread 41.

The shaft 50, as similar to that in the prior art of golf club, has a handle 51 and a lock hole 52 at the lower end and a thread section 52 in the middle section of  
25 the shaft 50.

Please refer to Figs 4 and 6 which show the adjustable tilt mechanism. First, the inner thread 41 of the retaining ring 40 is fitted in the thread section 53 of the shaft 50. The opening 31 of the hosel 30 will receive the shaft 50 section exposed under the retaining ring 40. When the lower end of the shaft 50 enters into the long adjustable hole 23 of the neck 21 of the head 20, the lock pin 26 will pass the lock hole 23 on the neck 21 and the lock hole 52 of the shaft 50. At this moment, the shaft 50 is permitted to swing to left or to right pivoted on the lock pin 26 within the adjustable hole 23 of the neck 21 to change the tilt (elevation angle) formed between the face 22 of the head 20 and the shaft 50.

10

Please refer to figs 4 and 5; when the shaft 50 is swung to left in the adjustable hole 23 of the neck 21, the elevation angle formed between the face 22 of the head 20, and the shaft 60 decreases. When the hosel 30 is pressed downward to the neck 21 of the head 20, the tie land 32 on the hosel opening 31 will be inserted into the tie slot 24 of the adjustable hole 23 (as shown in a closed position of Fig. 5), the shaft 50 along the retaining ring 40 and thread section 52 will move downward to hold the shaft 50 constantly fixed at the left position in the adjustable hole 23.

20 As shown in Figs. 6 and 7, if it is intended to increase the elevation angle between the face 22 of the head 20 and the shaft 50, the threaded section 53 and the retaining ring 40 are moved backward, so the hosel 30 will slide upward, and the tie land 32 of the hosel 30 will leave the tie slot 24 in the adjustable hole 23, so the lock pin 26 and the shaft 50 are free to swing to the right side.

25 When the hosel 30 is pressed downward to the neck top 21 of the head 20, the tie land 32 of the hosel opening 31 enters into the tie slot 24 in the adjustable

hole 23 (as shown in the closed position of Fig. 7), the retaining 40 and the threaded section 53 of the shaft 50 press on the adjustable hole 23 to hold the shaft 50 constantly fixed at the right position.

- 5    The above statement indicates that the adjustable tilt mechanism of the golf club is easy to adjust the elevation angle formed between the face of the head and the shaft which will render the ball a low or high parabola flight as the player desires to shun away the obstacle.
- 10   Many changes and modifications in the above disclosed embodiment of the invention can, of course, be carried out without departing from the scope thereof, such the shape of the long adjustable hole the number of the tie land and tie slot as desirable. Accordingly, to promote the progress in science and the useful arts, the invention is disclosed and is intended to be limited only by
- 15   the scope of the appended claims.